



定格荷重表

作業半径	30.0m	32.0m	35.0m	37.0m	40.0m	42.0m
0.0m	12.00t	12.00t				
0.4m			11.00t	11.00t		
0.8m					9.00t	9.00t
7.0m					9.00t	9.00t
8.0m					8.37t	8.59t
9.0m					7.84t	8.21t
10.0m					7.39t	7.85t
11.0m					7.00t	7.50t
12.0m					6.66t	7.17t
13.0m					6.37t	6.86t
14.0m					6.11t	6.56t
15.0m					5.87t	6.27t
16.0m					5.66t	6.00t
17.0m					5.47t	5.73t
18.0m				11.00t	5.30t	5.48t
19.0m			11.00t	10.46t	5.14t	5.24t
20.0m		12.00t	10.44t	9.94t	5.00t	5.00t
20.5m	12.00t	11.62t	10.18t	9.70t	4.92t	4.93t
21.0m	11.58t	11.26t	9.93t	9.46t	4.84t	4.86t
22.0m	10.84t	10.60t	9.45t	9.00t	4.71t	4.74t
23.0m	10.20t	10.00t	9.00t	8.56t	4.58t	4.62t
24.0m	9.64t	9.46t	8.58t	8.15t	4.47t	4.52t
25.0m	9.15t	8.96t	8.18t	7.75t	4.38t	4.42t
26.0m	8.70t	8.50t	7.80t	7.37t	4.29t	4.32t
27.0m	8.23t	8.02t	7.34t	7.00t	4.21t	4.24t
28.0m	7.80t	7.70t	6.97t	6.71t	4.13t	4.15t
29.0m	7.40t	7.46t	6.67t	6.48t	4.06t	4.07t
30.0m	7.00t	7.28t	6.41t	6.29t	4.00t	4.00t
31.0m		7.13t	6.19t	6.14t	3.94t	3.93t
32.0m		7.00t	6.00t	6.00t	3.89t	3.86t
33.0m			5.82t	5.88t	3.83t	3.80t
34.0m			5.66t	5.78t	3.78t	3.73t
35.0m			5.50t	5.68t	3.73t	3.67t
36.0m				5.59t	3.69t	3.61t
37.0m				5.50t	3.64t	3.55t
38.0m					3.60t	3.50t
39.0m					3.55t	3.44t
40.0m					3.50t	3.38t
41.0m						3.32t
42.0m						3.25t

仕様

名称				JCC-230Ⅱ (mkⅡ)					
定格荷重		t		12-7	12-7	11-5.5	11-5.5	9-3.5	9-3.25
作業半径		m		20.5-30	20-32	19-35	18-37	7-40	7-42
揚程		m		150					
速度	巻上	早巻	m/min	88.7-46.7/106.4-56.0 (1t以下-3t以下)					
		遅巻		27.8-14.6/33.3-17.5 (6t以下-12t以下)					
	起伏	sec	159/132						
	旋回	r.p.m	0.4/0.48						
	昇降	m/min	0.6/0.72 (押出) 0.3/0.36 (引込)						
電動機	巻上	kW		45					
	起伏			25					
	旋回			8.5					
	昇降			22					
操 作				運転室					
電源容量		kVA・A		150・350					
電 源	V	50/60Hz		200/220					