



名称		JCC-TS700S					
定格荷重	t	25.5-20	25.5-15.5	25.5-14	25.5-10.5	20-7.5	
作業半径	m	26.6-32	26.1-37	26.1-40	25.6-46	28.9-52	
揚 程	m		250		150		
速度	巻上	m/min					
	起伏	sec					
	旋回	r.p.m					
	昇降	m/min	50/60Hz	重負荷時：0.45/0.54(押出)、0.60/0.72(引込) 軽負荷時：1.03/1.24(押出)、1.37/1.66(引込)			
電 動 機	巻上	KW					
	起伏	132					
	旋回	55					
	昇降	18.5					
電 源	kVA・A		270・500				
	V	50/60Hz	400/440				
備 考							

作業半径	最大作業半径				
	32.0m	37.0m	40.0m	46.0m	52.0m
0.0m	11.50t	11.50t	11.50t	11.50t	11.50t
1.0m	15.48t	15.49t	15.49t	15.49t	13.92t
2.0m	19.48t	19.48t	19.49t	19.49t	16.35t
3.0m	23.49t	23.49t	23.49t	23.49t	18.78t
3.5m	25.50t	25.50t	25.50t	25.50t	20.00t
↓	↓	↓	↓	↓	↓
25.6m	↓	↓	↓	25.50t	↓
26.0m	↓	↓	↓	24.98t	↓
26.1m	↓	25.50t	25.50t	24.85t	↓
26.6m	25.50t	24.86t	24.87t	24.22t	↓
27.0m	25.00t	24.36t	24.39t	23.73t	↓
28.0m	23.84t	23.19t	23.25t	22.59t	↓
28.9m	22.88t	22.21t	22.29t	21.63t	20.00t
29.0m	22.78t	22.10t	22.19t	21.52t	19.90t
30.0m	21.80t	21.08t	21.20t	20.53t	18.97t
31.0m	20.90t	20.11t	20.27t	19.60t	18.10t
32.0m	20.00t	19.20t	19.40t	18.73t	17.28t
33.0m		18.39t	18.58t	17.91t	16.51t
34.0m		17.62t	17.80t	17.13t	15.77t
35.0m		16.90t	17.08t	16.40t	15.08t
36.0m		16.20t	16.40t	15.70t	14.42t
37.0m		15.50t	15.76t	15.04t	13.80t
38.0m			15.15t	14.43t	13.20t
39.0m			14.57t	13.85t	12.63t
40.0m			14.00t	13.31t	12.10t
41.0m				12.80t	11.60t
42.0m				12.31t	11.14t
43.0m				11.84t	10.70t
44.0m				11.39t	10.29t
45.0m				10.94t	9.90t
46.0m				10.50t	9.53t
47.0m					9.17t
48.0m					8.83t
49.0m					8.49t
50.0m					8.16t
51.0m					7.83t
52.0m					7.50t