



作業半径	最大定格荷重				
	32.0m	37.0m	42.0m	47.0m	52.0m
0.0m	11.5t	11.5t	11.5t	11.5t	11.5t
1.0m	15.9t	15.9t	15.9t	15.9t	14.1t
2.0m	20.3t	20.3t	20.3t	20.3t	16.8t
3.0m	24.7t	24.7t	24.7t	24.7t	19.5t
3.5m	27.0t	27.0t	27.0t	27.0t	22.2t
5.0m					25.0t
24.3m				27.0t	
24.5m					25.0t
25.0m				26.1t	24.3t
26.0m			27.0t	25.0t	23.1t
27.0m			25.8t	23.9t	21.9t
27.5m		27.0t			
27.8m	27.0t				
28.0m	26.7t	26.4t	24.7t	23.0t	20.8t
29.0m	25.6t	25.3t	23.7t	22.1t	19.9t
30.0m	24.5t	24.2t	22.8t	21.2t	18.9t
31.0m	23.5t	23.3t	21.9t	20.4t	18.1t
32.0m	22.5t	22.3t	21.1t	19.7t	17.2t
33.0m		21.5t	20.3t	19.0t	16.5t
34.0m		20.7t	19.6t	18.4t	15.7t
35.0m		19.9t	18.9t	17.8t	15.0t
36.0m		19.2t	18.2t	17.2t	14.4t
37.0m		18.5t	17.6t	16.6t	13.8t
38.0m			17.1t	16.1t	13.2t
39.0m			16.5t	15.6t	12.6t
40.0m			16.0t	15.2t	12.1t
41.0m			15.5t	14.8t	11.6t
42.0m			15.0t	14.3t	11.1t
43.0m				14.0t	10.7t
44.0m				13.6t	10.2t
45.0m				13.2t	9.9t
46.0m				12.8t	9.5t
47.0m				12.5t	9.1t
48.0m					8.8t
49.0m					8.4t
50.0m					8.1t
51.0m					7.8t
52.0m					7.5t

名称		JCC-TS750S					
定格荷重	t	22.5 - 11.5	18.5 - 11.5	15.0 - 11.5	12.5 - 11.5	7.5 - 11.5	
作業半径	m	32	37	42	47	52	
揚程	m	250m					
速度	巻上	114.7 - 25.7					
	起伏	107	106	105	107	111	
	旋回	0.48					
	昇降	50/60Hz					
電動機	巻上	132					
	起伏	55					
	旋回	18.5					
	昇降	22					
操作		運転室					
電源容量		300・400					
電源		50/60Hz					