



定格荷重表

	R-27m	R-32m	R-36m	R-41m	R-45m
3m	13.00	13.00	13.00	10.00	8.00
16m	↓	↓	↓	↓	8.00
17m	↓	↓	↓	↓	7.70
18m	↓	↓	↓	↓	7.50
19m	↓	↓	13.00	10.00	7.20
20m	↓	13.00	12.40	9.70	6.90
21m	13.00	12.70	11.80	9.30	6.70
22m	12.70	12.10	11.30	9.00	6.40
23m	12.10	11.50	10.80	8.70	6.20
24m	11.60	11.00	10.30	8.40	6.00
25m	11.10	10.50	9.80	8.10	5.70
26m	10.60	10.00	9.40	7.80	5.50
27m	10.00	9.50	8.90	7.50	5.30
28m	9.10	8.50	7.30	5.10	
29m	8.70	8.10	7.00	4.90	
30m	8.30	7.80	6.70	4.70	
31m	7.90	7.40	6.50	4.50	
32m	7.50	7.10	6.20	4.30	
33m		6.80	6.00	4.10	
34m		6.50	5.80	4.00	
35m		6.30	5.60	3.80	
36m		6.00	5.40	3.70	
37m			5.20	3.50	
38m			5.00	3.40	
39m			4.80	3.20	
40m			4.70	3.10	
41m			4.50	3.00	
42m				2.80	
43m				2.70	
44m				2.60	
45m				2.50	

仕様

ジブ長さ		R27mJib	R32mJib	R36mJib	R41mJib	R45mJib
速	巻上	50Hz/60Hz	1.2t~13.0t		1.417~0.350m/sec (85~21m/min)	
	起伏	50Hz/60Hz	80~85 sec			
	旋回	50Hz/60Hz	0.050 rad/sec (0.48 rpm)			
度	昇降	50Hz	8.333 × 10 <sup>-3</sup> m/sec (0.50 m/min)			
		60Hz	10.000 × 10 <sup>-3</sup> m/sec (0.60 m/min)			
電動機	巻上	55.0kW 4P 40%ED インバーター制御				
	起伏	34.5kW 4P 40%ED インバーター制御				
	旋回	14.3kW 4P 25%ED インバーター制御				
	昇降	18.5kW 4P Cont				
揚程	最大半径時	R45mJib			100 m	
		R41mJib~R27.0mJib			150 m	
タワー自立高さ	45.0m自立					
操作方式	運転室内操作					
クライミング方式	油圧クライミング方式					
電源	400/440V 50/60Hz					
安全装置	巻過防止装置、起伏制限装置、過負荷防止装置					
解体重量	6.0m強化タワー 約7.5 t					