



仕様

名称		OTA-480HN	
揚程	m	258m	
速度	巻上	m/min	28 - 128
	起伏	sec	10.3 - 107
	旋回	r.p.m	0.44
	昇降	m/min	50/60Hz
電動機	巻上	kW	110
	起伏		39
	旋回		19.5
	昇降		22
操作		運転室	
電源容量	kVA・A	250・400	
電源	V	50/60Hz	
電 源	V	400/440	

定格荷重表

作業半径	最大定格荷重				
	32.0m	36.0m	41.0m	45.0m	50.0m
0.0m	10.0t	10.0t	10.0t	10.0t	10.0t
1.0m	13.3t	13.3t	13.3t	11.5t	↓
2.0m	16.7t	16.7t	16.7t	13.0t	↓
3.0m	20.0t	20.0t	20.0t	14.5t	↓
4.0m	↓	↓	↓	16.0t	↓
↓	↓	↓	↓	↓	↓
20.0m	↓	↓	↓	16.0t	10.0t
21.0m	↓	↓	↓	15.3t	9.6t
22.0m	↓	↓	20.0t	14.7t	9.2t
23.0m	↓	20.0t	19.1t	14.1t	8.8t
24.0m	20.0t	19.3t	18.3t	13.5t	8.5t
25.0m	19.3t	18.5t	17.5t	13.0t	8.1t
26.0m	18.5t	17.7t	16.7t	12.5t	7.8t
27.0m	17.8t	16.9t	16.0t	12.0t	7.5t
28.0m	17.0t	16.0t	15.3t	11.6t	7.2t
29.0m	16.3t	15.4t	14.7t	11.2t	7.0t
30.0m	15.5t	14.8t	14.1t	10.8t	6.7t
31.0m	14.8t	14.3t	13.5t	10.4t	6.5t
32.0m	14.0t	13.7t	13.0t	10.0t	6.2t
33.0m		13.2t	12.5t	9.7t	6.0t
34.0m		12.6t	12.0t	9.4t	5.7t
35.0m		12.1t	11.7t	9.1t	5.4t
36.0m		11.6t	11.3t	8.9t	5.2t
37.0m			11.0t	8.7t	5.0t
38.0m			10.7t	8.5t	4.8t
39.0m			10.3t	8.3t	4.7t
40.0m			10.0t	8.2t	4.6t
41.0m			9.6t	8.1t	4.5t
42.0m				7.9t	4.4t
43.0m				7.8t	4.3t
44.0m				7.7t	4.3t
45.0m				7.6t	4.2t
46.0m					4.2t
47.0m					4.1t
48.0m					4.1t
49.0m					4.0t
50.0m					4.0t

